

Pro Regul®

Amperometric regulator + pH regulator
for saltwater chlorinator



Pro Regul® can be paired with a chlorinator or a dosing pump (liquid chlorine) with a Chlore Fresh or Chlore Salt probe depending on the type of device.



S T I F E N E B

Analysis and regulation using a chlorine probe

pecially developed for saltwater chlorination

pH injection proportional to the deviation

between the setpoints and the probe measurements

Panel-mounted system

ready to install, easy to commission

High quality pH Blue and Cl Salt probes

factory tested and calibrated

Limits the risk of overchlorination

and protects equipment (cover, liners, etc.)

Intuitive navigation

on a wide-angle screen



Connectivity

e-Pool® app and connected pool compatible

FEATURES

Chlorine production control by amperometric probe

Proportional pH regulation in acid (pH -) or basic (pH+) mode

Display of water temperature and salt level

Settings: pH injection cycles, pH and Cl setpoints ranges, high/low thresholds, alarms

Log of events

Multilingual communication interface

Alarm messages: origin of the malfunction indicated by a written message

Safeties and information: high and low Cl and pH values, Cl and pH setpoints not reached, Cl and pH setpoint ranges exceeded, pH can empty

TECHNICAL SPECIFICATIONS

Screen: IPS HD panel

Correction product: pH- or pH+

Type of pH regulation: proportional

pH set point adjustment: 6.8 to 7.6

pH probe calibration: 2 points pH 7 and pH 10

pH probe: Blue

Free chlorine set point adjustment: 0.1 to 8 ppm

Cl probe: Chlorine Salt

Box dimensions: W 140 x H 300 x D 97 mm

Panel dimensions: W 545 x H 450 x D 110 mm



1 Pre-filter with cartridge
washable polyester 50 µm

2 pH Blue probe
MESU003003-PDC


3 Chlorine Salt probe
MESU003104-PDC2

4 Measuring chamber
made of transparent PMMA

3 Integrated flow sensor
to guarantee pH value

6 Peristaltic pump 6 L/h

PRINCIPLE DIAGRAM



CONTENT

Panel-mounted electronic box and Ampero/pH measuring chamber + peristaltic pump
Amperometric measuring chamber connection kit
Chlorine Salt probe
pH Blue Probe
pH 7 & pH 10 calibration solutions
pH injection fitting
Salt/temperature sensor + saddle clamp Ø 63 mm
Measuring chamber flow sensor
Suction pipe with empty pH can sensor
Power cable (2 m)
User manual

WARRANTIES

Box: 2 years
pH Blue probe: 1 year
CI Salt probe: 1 year

REFERENCE

COAP23POOC-G5